

NX-3720HG/3820HG

VHF/UHF MULTI-PROTOCOL DIGITAL & ANALOG MOBILE RADIOS

This adaptable mobile radio supports both NXDN® and DMR digital protocols as well as mixed digital/FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation-critical applications. Designed with flexibility in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. This model offers greater freedom of installation, the radio's front panel can be used as a remote control head (this requires an optional upgrade, to be available in the future). Additionally, for expansion capability a software license certification system facilitates extensive customization.

FEATURES

- Multi-protocol digital radio: Designed to operate under NXDN® or DMR digital, and FM analog protocols
- NXDN Conventional and Type-C & Gen2 Trunking
- DMR Tier II & Site Roaming
- Mixed Digital & FM Analog Operation allows gradual migration at your own pace
- 4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- 4-Line Text Message Frame (2 Lines of Text, icon & key guide)
- 7-color LED indicator
- External and Internal Speaker Switching
- Built-In GPS Receiver for effective fleet management
- Built-in Bluetooth® for hands-free operation - Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option; availability depends on the model)
- Renowned KENWOOD Audio Quality with Active Noise Reduction (ANR) that utilizes built-in DSP

- IP54 and MIL-STD-810 C/D/E/F/G
- 4 Watts Audio Output Power
- 512 CH/128 Zones
- 1000 Channel option
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

DIGITAL – NXDN® MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Software DES and AES Encryptions for NXDN Conventional/Trunking and DMR Conventional protocols
- 12.5 kHz Two-slot TDMA channels
- Call Interruption
- Dual-slot Direct Mode
- Optional ARC4 Encryption

ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / TextMessages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone
- Built-in Voice Inversion Scrambler



Multi-Protocol

Unsurpassed interoperability for Public Safety and Enterprise radio users with the freedom to migrate at your own pace.



Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.



Klarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

<ul style="list-style-type: none"> ■ KMC-9C/59C Desktop Microphone ■ KMC-35 Microphone ■ KMC-36 Keypad Microphone ■ KES-3S External Speaker (compact low profile; 3.5 mm plug) 	<ul style="list-style-type: none"> ■ KES-5 External Speaker (40 W max input, requires KAP-2) ■ KCT-18 Ignition Sense Cable (Requires KCT-60) ■ KCT-23 DC Power Cable M: 10ft (3m) / M3: 23ft (7m) 	<ul style="list-style-type: none"> ■ KCT-60 Connection Cable (D-sub 15 to Molex 15 Pin Connector) ■ KLF-2 Line Filter ■ KMB-10 Key Lock Adapter ■ KRA-40G GPS Active Antenna 	<ul style="list-style-type: none"> ■ KPS-15 DC Power Supply (23A max) ■ KMB-34 Mounting Case for KPS-15 ■ KPG-180AP OTAP Manager
--	---	--	--

All accessories may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories.

Specifications

	NX-3720HG	NX-3820HG
GENERAL		
Frequency Range	136-174 MHz	Type 1 450-520 MHz Type 2 400-470 MHz
Max. Channels Per Radio	Up to 1,000 CH with option	
Number of Channels	512	
Number of Zones	128	
Channel Spacing		
Analog	12.5/15/20/25*/30* kHz	12.5/25* kHz
Digital	6.25/12.5 kHz	6.25/12.5 kHz
Power Supply	13.6 V DC ±15%	
Current Drain		
Standby	0.45 A	
RX	2.3 A	
TX	12 A	
Operating Temperature	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability	±1.0 ppm	
Antenna Impedance	50 Ω	
Dimensions	(W x H x D) Projections Not Included	
Radio w/Control Head	6.30 x 1.69 x 6.30 in (160 x 43 x 160 mm)	
Weight (net)	2.65 lbs (1.2 kg)	
FCC ID		
Type 1	K44479200	K44479300
Type 2	-	K44479301
IC Certification		
Type 1	282F-479200	-
Type 2	-	282F-479301

	NX-3720HG	NX-3820HG
RECEIVER		
Sensitivity		
NXDN® 6.25 kHz Digital (3% BER)		0.20 μV
NXDN® 12.5 kHz Digital (3% BER)		0.25 μV
DMR 12.5 kHz Digital (5% BER)		0.30 μV
DMR 12.5 kHz Digital (1% BER)		0.45 μV
Analog (12dB SINAD)		0.25 μV
Selectivity		
Analog @ 12.5 kHz		70 dB
Analog @ 25 kHz		80 dB
Intermodulation		70 dB
Audio Distortion		2 %
Audio Output Power		4 W/4 Ω
TRANSMITTER		
RF Power Output (High / Mid / Low)	50 W / 30 W / 5 W	45 W /30 W / 5 W
Spurious Emission	73 dB	75 dB
FM Hum & Noise		
Analog @ 12.5 kHz		45 dB
Analog @ 25 kHz		40 dB
Audio Distortion		2%
Digital Protocol	ETSI TS 102 361-1, -2, -3	
Emission Designator	16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

*1 25 and 30 kHz are not included in the models sold in the USA or US territories. Analog measurements made per TIA603. Specifications are measured according to applicable standards. Specifications shown are typical and subject to change without notice, due to advancements in technology.

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc. NEXEDGE® & FleetSync® are a registered trademarks of JVCKENWOOD Corporation. All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V	516.6/Procedure I, IV, V
International Protection Standard					
Dust & Water*	IP54 (Radio unit)				

*Microphone KMC-35 or KMC-36 must be connected to the radio, and all accessory connectors must be covered.



JVCKENWOOD USA Corporation
Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

www.kenwood.com/usa

JVCKENWOOD Canada Inc.

Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

www.kenwood.com/ca



ISO9001 Registered

JVCKENWOOD Corporation

ADS#37617 Printed in USA